

Product Data Sheet

DC1500V Switch Disconnecter

HGL 08K

General Information & Ratings

Product Code	HGL08 (K Frame)
Rated Current [In max, 40°C]	800A
Number of Poles	3, 4P
Operation Temperature	-4°F to +140°F (-20°C to +60°C)
Installation Type	Fixed Type Draw-Out Type

Characteristics

Rated Nominal Voltage		1,250Vdc (4P) / 800Vdc (3P)
Rated Maximum Voltage		1,500Vdc (4P) / 1,000Vdc (3P)
Short Circuit Withstand Current [kA]	1s	85
	0.6s	-
Rated Short Circuit Making Capacity [Icm]		100 (kA, peak)
Motor Charging Time (sec) max		10
Closing Time (ms) max		80
Life Cycle (Cycles)	Mechanical	12,500
	Electrical	3,500
Material of Main Contacts		Ag
Material of Arcing Contacts		Cu
Operating Time For Shunt Trip Coil (fully open)		35 ms
Operation Time Closing Coil (fully open)		80 ms

Environment

Altitude above sea level	≤ 2000m
Relative humidity to be within	≤ 85%

Standards & Certifications

Certification	UL 489, UL 489B
---------------	-----------------

Dimension & Installation

Fixed Type (3P)	Width (inch)	13.91	
	Height (inch)	15.92	
	Depth (inch)	11.65	
	Weight (lb)	88	
Draw-out Type (3P)	Width (inch)	12.91	
	Height (inch)	19.17	
	Depth (inch)	16.54	
	Weight (lb)	161	
Phase-to-Phase Clearance (inch)		Vertical type	3.35
Phase-to-Ground Clearance (inch)		Vertical type	3.35
Main Contact Gap (mm)		30	
Arcing Contact Gap (mm)		36	
Country of Origin		South Korea	

