

Product Data Sheet

Molded Case Circuit Breakers

HGU400L/ LT 3P

General Information & Ratings

Product Code	HGU400L/ LT 3P4T	
Rated Current [In]	250, 300, 350, 400A, at 40°C (104°F)	
Number of Poles	3P	
Trip Units	MTM (Thermal-fixed, Magnetic-fixed)	
	MTM (Thermal-adjustable, Magnetic-fixed)	
	MTM (Thermal-adjustable, Magnetic-adjustable)	
	MCP (Motor Circuit Breaker)	
MCS (Molded case switch)		
Rated Frequency [Hz]	50 / 60Hz	
Terminal Mountings	Line side	Lug or Bolt
	Load side	Lug or Bolt

Characteristics

UL Rated	80% (L), 100% (LT)
Mechanical Durability	5,000 cycles
Electrical Durability	1,000 cycles
Interrupting Capacity (kA, rms)	150kA at 240Vac 50/60Hz
	100kA at 480Vac 50/60Hz
	65kA at 600Vac 50/60Hz
[LTD]Thermal magnetic Long time Adjustment Range	0.8-0.9-1.0 x In (3 steps)
[INST]Thermal magnetic Instantaneous Adjustment Range	5-6-7-8-9-10 x In (6 steps)
Accessories	Auxiliary switch
	Alarm switch
	Shunt trip
	Under Voltage trip
	Mechanical interlocks
	Handle Padlock Attachment
	Direct rotary handle mechanism (Type1)
	Variable depth rotary handle mechanism (Type1)
	Variable depth rotary handle mechanism (1 - 4X)
	Flange cable handle
	Flange variable-depth handle

Environment

Ambient air temperature for operation	-5 °C to 40 °C (23°F to 104°F)
Altitude above sea level	≤ 2,000m (6,562 ft)
Relative humidity to be within	45 to 85 %

Standards & Certifications

Certification	UL489
---------------	-------

Dimensions

Product, inch (Width x Height x Depth)	5.51 x 11.4 x 4.33
Individual Box Packing, inch (Width x Height x Depth)	6.89 x 14.76 x 7.48
Weight (lb)	13.23
Country of Origin	South Korea

