


Customer :

Project Name :

Project No. :

Revision No. :

SPECIFICATION for INDUCTION MOTOR



0		For Bidding			
No.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY

AC INDUCTION MOTOR DATA SHEET

IEEE841 TYPE

Catalog No.	IEEEV1.5-18-145TCRD	Item No.		Rev. No.	[]
Project Name		Project No.		Quantity	sets

GENERAL SPECIFICATION			PERFORMANCE DATA			
Frame Size		145TC	Rated Output		1.1 kW 1.5 HP	
Type		PJP	Number of Poles		4	
Enclosure(Protection)		Totally Enclosed / IP55	Rotor Type		Squirrel Cage	
Method of Cooling		IC411(FC)	Starting Method*		D.O.L	
Rated Frequency		60 Hz	Rated Voltage		575 V	460 V 230 V
Number of Phases		3	Current	Full Load	1.77 A	2.22 A 4.43 A
Insulation Class		F		Locked-rotor**	900 %	900 % 900 %
Temp. Rise at full load (by resistance method)			Efficiency			
	at 1.0 S.F	80 deg. C		50% Load	83.5 %	
Motor Location		☐ Indoor ☐ Outdoor		75% Load	85.5 %	
Altitude		Less than 1,000 meter		100% Load	86.5 %	
Relative Humidity		Less than 80 %	Power Factor(p.u)			
Ambient Temp.		40 deg. C (Max.)		50% Load	0.570	
Duty Type		Continuous (S1)		75% Load	0.670	
Service Factor		1.15		100% Load	0.720	
Mounting		B5	Speed at Full Load		1750 r.p.m	
Bearing	Type	Anti-Friction	Torque			
	DE/N-DE	6205ZC3 / 6204ZC3		Full Load	4.43 lb.ft	
	Lubricant	Grease(Polyrex-EM)		Locked-rotor**	260 %	
External Thrust		Not applicable		Breakdown**	290 %	
Coupling Method		☒ Direct ☐ V-belt	Moment of Inertia (J)			
Shaft Extension		Single		Load(Max.)	11.865 lb.ft2	
Terminal	Main	Cast Iron		Motor	0.076 lb.ft2	
Box	Aux.	No	Sound Pressure Level (No-load & mean value at 1m from motor)			
	Location	Refer to Outline Drawing			56 dB(A)	
Application			Vibration		2.03 mm/s (peak)	
Area classification		Hazardous	Permissible number of		Cold 3 times	
Type of Ex-Protection		Class I&II, Division 2	consecutive starts		Hot 2 times	
Applicable Standard		IEEE841, NEMA MG1, CSA C390	Paint	Munsell No.	7.5BG6/1.5	

ACCESSORIES		SUBMITTAL DRAWING					
		Outline Dimension Drawing \ Motor Weight(Approx.)					
		B5		LM-I2145C5PLV23	60 lb.		
		REMARK					
SPARE PARTS		1. Premium efficiency according to NEMA MG1					
		2. Inverter Duty @ 1.0 Service Factor & F Temperature rise					
		- 10:1 VT (20:1 VT at 50% load)					
		- 10:1 CT					
		- CHP up to 1.5 times base speed, NEMA MG1 Part31					
		3. CSA Certification					
		- Class I, Division 2, Group A, B, C & D					
		- Class II, Division 2 Group E, F & G (Group E : up to 320Fr.)					
		4. Service Factor 1.15 and Temperature rise B are applicable under the condition of sine wave power.					
		5. Service Factor 1.25 is applicable to motors of 100HP or less with temperature rise F & Non-Hazardous.					
		6. Temp. code : T3C(160°C) at sine wave					
		Date		DSND	CHKD	CHKD	APPD
		2025-09-19		S.H. LEE	I.K. KIM	R.G. KIM	S.W. KIM

[Note] Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be done according to maker standard, if not mentioned.

* In case of Inverter-Fed Motor, performance data is based on sine wave tests. It may be different from test data of Inverter combined motor.

** Data is based on rated voltage & frequency and is expressed as a percentage of full-load value.

MAIN NAMEPLATE

3.94

1.57

CROWN TRITON G2 Premium Efficiency AC 3 Phase Motor				Cat. No. IEEEV1.5-18-145TCRD						
1.5HP	4P	460V	Amps	2.22A	Type	HLS	Amb.	40°C		
Frame	145TC	Duty	CONT	Encl.	TEFC	Model	HLS145PR238V	NEMA Nom. Eff.	86.5%	
RPM	1750	Hertz	60Hz	S.F.	1.15	INS. Class	F	3/4 Eff.	85.5%	
		Drive	6205ZC3	S.F.1.25 (When 100HP or less, Temp Rise F & Non-Hazardous)				NEMA Design	B	
		Opp.	6204ZC3	S.F.1.00 (10:1 C.T., 20:1 V.T., NEMA-MG1 Part31)				Code	L	
Bearing	Usable at									
	50Hz 1.5HP 380V 2.77A 1440rpm S.F.: 1.15 Eff.: 83.9% Code: J									
	50Hz 1.5HP 400/415V 2.72/2.71A 1445/1450rpm S.F.: 1.15 Eff.: 84.0/84.0% Code: K/L									
CSA Certified for	Model	-	Type	PJP	Temp. Code	Frame	140~320FR	CE		
	CLASS I, Div. 2, Gr. A, B, C & D	CLASS II, Div. 2, Gr. E, F & G			(Sine Wave)	Amb.40°C	T3C (160°C)			
	CLASS I, Zone 2, Gr. IIA, IIB & IIC	(Gr. E : up to 320FR)				Amb.55°C	T3A (180°C)			
No.	-	Date	-	Weight	60 lb					
MARINE DUTY IEEE45 IEEE Std 841-2021		4M-138277	Made in Vietnam H4 Designed By HYUNDAI, Korea		HD HYUNDAI ELECTRIC					

WIRING DIAGRAM


D.O.L (INVERTER & SOFT STARTER)	WYE-DELTA (Y-D)
WARNING IMPROPER INSTALLATION, CONNECTION, OPERATION, GROUNDING OF THIS MOTOR MAY CAUSE SERIOUS INJURY TO PERSONNEL OR MOTOR FAILURE. READ INSTRUCTIONS CAREFULLY. GROUNDING SHOULD BE IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE AND APPLICABLE LOCAL SOUND PRACTICES. T1 L1 T2 L2 T3 L3 KEEP FINGERS AND FOREIGN OBJECTS AWAY FROM OPENINGS AND ROTATING PARTS DISCONNECT ALL POWER SOURCES BEFORE TOUCHING INTERNAL PARTS TO AVOID ELECTRICAL SHOCK. 4M-128796	N/A

APPD BY	S.Y.KIM	UNIT	INCH	SUBJECT	CSA Class I, Division2 IEEE841 (SSEN, 143-215)	DWG SIZE	A4 (1:1)
CHKD BY	I.K.KIM	SCALE	NONE	NAMEPLATE DRAWING			
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle				
DSND BY	S.H.LEE	DATE	2024.06.07				
				REF. NO	4M-138277 / 4M-128796	Sheet No.	of
				DWG NO	NP-IEEEV1.5-18-145TCRD	Revision No.	0


Type :	PJP	
Full Load Torque :	4.43	lb.ft
Load moment of Inertia (J) :	11.865	lb.ft2
Motor moment of Inertia (J) :	0.076	lb.ft2

1.1kW	1.5HP	4 P	60 Hz
Speed at Full Load :			1750 RPM
Rated Voltage	575V	460V	230V
Full Load Current	1.77A	2.22A	4.43A

SPEED VS TORQUE & CURRENT CURVE





OUTPUT VS EFF., P.F & CURRENT CURVE



1	2	3	4
▽	50S	REV	DATE
▽▽	12.5S		
▽▽▽	3.2S		
▽▽▽▽	0.4S		

IEEE841




DETAIL - B

NOTE

[TOLERANCE]

- CENTER HEIGHT : +0.00inch - 0.03inch
- SHAFT DIAMETER : +0.000inch - 0.0005inch
- KEYWAY DEPTH : +0.000inch - 0.015inch




SECTION "X-X"

SCALE 5/6

APPD BY	S.Y.KIM	UNIT	inch	SUBJECT	NEMA 145TC	DWG SIZE
CHKD BY	R.G.KIM	SCALE	1/5			A4 (15)
CHKD BY		PROJEC'N	3rd Angle	TITLE	OUTLINE	
DSND BY	주유림	DATE	2021-04-28	REF. NO		Sheet No. of
				DWG NO	LM-I2145C5PLV23	Revision No. 0

Cls. I&II, Div. 2

IEEE 841



▽	50S
▽▽	12.5S
▽▽▽	3.2S
▽▽▽▽	0.4S

REV	DATE	CONTENTS	REV'D BY	CHK'D BY	CHK'D BY	APP'D BY
1						

일반가공공차		일반재공공차	
1-4	±0.1	6-30	±0.5
4-18	±0.2	30-120	±0.8
18-63	±0.3	120-315	±1.2
63-250	±0.5	315-1000	±2.0
250-	±0.8	1000-	±3.0

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APP'D BY	S.Y.KIM	UNIT	inch(mm)	SUBJECT	FR. 140-180 (CAST IRON)	DWG SIZE	
CHK'D BY		SCALE	1/1.5	TITLE	TERMINAL BOX ASS'Y	A3 (1:1.5)	
CHK'D BY	R.G.KIM	PROJEC'N	3rd Angle	REF. NO		Sheet No. of	
DSND BY	네슬희	DATE	2023-10-19	DWG NO	3M-248456	Revision No. 0	

