

Customer :
Project Name :
Project No. :
Revision No. :

SPECIFICATION for INDUCTION MOTOR



0		For Bidding			
No.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY

AC INDUCTION MOTOR DATA SHEET

Catalog No.	HES1.5-18-145TCRD	Item No.			Rev. No.	[]	
Project Name		Project No.			Quantity	sets	
GENERAL SPECIFICATION				PERFORMANCE DATA			
Frame Size	145TC		Rated Output	1.1 kW		1.5 HP	
Type	PJP		Number of Poles	4			
Enclosure(Protection)	Totally Enclosed / IP55		Rotor Type	Squirrel Cage			
Method of Cooling	IC411(FC)		Starting Method*	D.O.L			
Rated Frequency	60 Hz		Rated Voltage	575 V	460 V	230 V	
Number of Phases	3		Current	Full Load	1.77 A	2.22 A	4.43 A
Insulation Class	F			Locked-rotor**	900 %	900 %	900 %
Temp. Rise at full load (by resistance method)			Efficiency				
at 1.0 S.F			80 deg. C				
Motor Location	☐ Indoor ☐ Outdoor		50% Load		83.5 %		
Altitude	Less than 1,000 meter		75% Load		85.5 %		
Relative Humidity	Less than 80 %		100% Load		86.5 %		
Ambient Temp.	40 deg. C (Max.)		Power Factor(p.u)				
Duty Type	Continuous (S1)		50% Load		0.570		
Service Factor	1.15		75% Load		0.670		
Mounting	B5		100% Load		0.720		
Bearing	Type	Anti-Friction	Speed at Full Load		1750 r.p.m		
	DE/N-DE	6205ZZC3 / 6204ZZC3	Torque				
	Lubricant	Grease(Polyrex-EM)	Full Load		4.43 lb.ft		
External Thrust	Not applicable		Locked-rotor**		260 %		
Coupling Method	☒ Direct ☐ V-belt		Breakdown**		290 %		
Shaft Extension	Single		Moment of Inertia (J)				
Terminal	Main	Cast Iron	Load(Max.)		11.865 lb.ft2		
Box	Aux.	No	Motor		0.076 lb.ft2		
	Location	Refer to Outline Drawing	Sound Pressure Level (No-load & mean value at 1m from motor)				
Application			56 dB(A)				
Area classification	Hazardous		Vibration		3.8 mm/sec (peak)		
Type of Ex-Protection	Class I&II, Division 2		Permissible number of consecutive starts		Cold 3 times Hot 2 times		
Applicable Standard	NEMA MG1, CSA C390		Paint	Munsell No.	4.0PB5.4/5.5(VL-451)		
ACCESSORIES			SUBMITTAL DRAWING				
			Outline Dimension Drawing \ Motor Weight(Approx.)				
			B5		LM-T2145C5PLV23	60 lb.	
SPARE PARTS			REMARK				
			1. Premium efficiency according to NEMA MG1 2. Inverter Duty @ 1.0 Service Factor & F Temperature rise -. 10:1 VT (20:1 VT at 50% load) -. 10:1 CT -. CHP up to 1.5 times base speed, NEMA MG1 Part31 3. CSA Certification -. Class I, Division 2, Group A, B, C & D -. Class II, Division 2 Group E, F & G (Group E : up to 320Fr.) 4. Service Factor 1.15 and Temperature rise B are applicable under the condition of sine wave power. 5. Service Factor 1.25 is applicable to motors of 100HP or less with temperature rise F & Non-Hazardous. 6. Temp. code : T3C(160°C) at sine wave				
			Date	DSND	CHKD	CHKD	APPD
			2025-07-22	S.H. LEE	I.K. KIM	R.G. KIM	S.W. KIM

[Note] Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be done according to maker standard, if not mentioned.


* In case of Inverter-Fed Motor, performance data is based on sine wave tests. It may be different from test data of Inverter combined motor.

** Data is based on rated voltage & frequency and is expressed as a percentage of full-load value.


Type :	PJP	
Full Load Torque :	4.43	lb.ft
Load moment of Inertia (J) :	11.865	lb.ft2
Motor moment of Inertia (J) :	0.076	lb.ft2

1.1kW	1.5HP	4 P	60 Hz
Speed at Full Load :			1750 RPM
Rated Voltage	575V	460V	230V
Full Load Current	1.77A	2.22A	4.43A



SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE




1			2		3		4		
▽	50S	REV	DATE	CONTENTS		REVD BY	CHKD BY	CHKD BY	APPD BY
▽▽	12.5S								
▽▽▽	3.2S								
▽▽▽▽	0.4S								



NOTE
[TOLERANCE]


- CENTER HEIGHT : +0.00inch - 0.03inch
- SHAFT DIAMETER : +0.000inch - 0.0005inch
- KEYWAY DEPTH : +0.000inch - 0.015inch



APPD BY	S.Y.KIM	UNIT	inch	SUBJECT	NEMA 145TC	DWG SIZE
CHKD BY	R.G.KIM	SCALE	1/5	TITLE OUTLINE		A4 (15)
CHKD BY		PROJEC'N	3rd Angle			
DSND BY	주유림	DATE	2021-04-28			
				REF. NO		Sheet No. of
				DWG NO	LM-T2145C5PLV23	Revision No. 0

Cls. I&II, Div. 2

IEEE 841



▽	50S
▽▽	12.5S
▽▽▽	3.2S
▽▽▽▽	0.4S

REV	DATE	CONTENTS	REV'D BY	CHK'D BY	CHK'D BY	APP'D BY
1						
2						
3						
4						

일반가공공차		일반재공공차	
1-4	±0.1	6-30	±0.5
4-18	±0.2	30-120	±0.8
18-63	±0.3	120-315	±1.2
63-250	±0.5	315-1000	±2.0
250-	±0.8	1000-	±3.0

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APP'D BY	S.Y.KIM	UNIT	inch(mm)	SUBJECT	FR. 140-180 (CAST IRON)	DWG SIZE	
CHK'D BY		SCALE	1/1.5	TITLE	TERMINAL BOX ASS'Y	A3 (1:1.5)	
CHK'D BY	R.G.KIM	PROJEC'N	3rd Angle	REF. NO		Sheet No.	of
DSND BY	네슬피	DATE	2023-10-19	DWG NO	3M-248456	Revision No.	0

