

Customer :

Project Name :

Project No. :

Revision No. :

SPECIFICATION for INDUCTION MOTOR



0		For Bidding			
No.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY

www.hd-hyundaelectric.com

AC INDUCTION MOTOR DATA SHEET

Catalog No.	HES7.5-36-213/5JP	Item No.			Rev. No.	[]	
Project Name		Project No.			Quantity	sets	
GENERAL SPECIFICATION				PERFORMANCE DATA			
Frame Size	215JP		Rated Output	5.5 kW		7.5 HP	
Type	PJP		Number of Poles	2			
Enclosure(Protection)	Totally Enclosed / IP55		Rotor Type	Squirrel Cage			
Method of Cooling	IC411(FC)		Starting Method*	D.O.L			
Rated Frequency	60 Hz		Rated Voltage	575 V	460 V	230 V	
Number of Phases	3		Current	Full Load	7.26 A	9.07 A	18.1 A
Insulation Class	F			Locked-rotor**	700 %	700 %	700 %
Temp. Rise at full load (by resistance method)			Efficiency				
at 1.0 S.F			80 deg. C				
Motor Location	☐ Indoor ☐ Outdoor		50% Load		86.5 %		
Altitude	Less than 1,000 meter		75% Load		88.5 %		
Relative Humidity	Less than 80 %		100% Load		89.5 %		
Ambient Temp.	40 deg. C (Max.)		Power Factor(p.u)				
Duty Type	Continuous (S1)		50% Load		0.700		
Service Factor	1.15		75% Load		0.800		
Mounting	B35		100% Load		0.850		
Bearing	Type	Anti-Friction	Speed at Full Load		3530 r.p.m		
	DE/N-DE	6309ZZC3 / 6208ZZC3	Torque				
	Lubricant	Grease(Polyrex-EM)	Full Load		10.98 lb.ft		
External Thrust	Not applicable		Locked-rotor**		160 %		
Coupling Method	☒ Direct ☐ V-belt		Breakdown**		260 %		
Shaft Extension	Single		Moment of Inertia (J)				
Terminal	Main	Cast Iron	Load(Max.)		11.159 lb.ft2		
Box	Aux.	No	Motor		0.451 lb.ft2		
	Location	Refer to Outline Drawing	Sound Pressure Level (No-load & mean value at 1m from motor)				
Application			73 dB(A)				
Area classification	Hazardous		Vibration		3.8 mm/s (peak)		
Type of Ex-Protection	Class I&II, Division 2		Permissible number of consecutive starts		Cold	3 times	
Applicable Standard	NEMA MG1, CSA C390				Hot	2 times	
			Paint	Munsell No.	4.0PB5.4/5.5(VL-451)		
ACCESSORIES			SUBMITTAL DRAWING				
			Outline Dimension Drawing \ Motor Weight(Approx.)				
			B35	LM-T2215C4JLV25	190 lb.		
			REMARK				
			1. Premium efficiency according to NEMA MG1 2. Inverter Duty @ 1.0 Service Factor & F Temperature rise -. 10:1 VT (20:1 VT at 50% load) -. 10:1 CT -. CHP up to 1.5 times base speed, NEMA MG1 Part31 3. CSA Certification -. Class I, Division 2, Group A, B, C & D -. Class II, Division 2 Group E, F & G (Group E : up to 320Fr.) 4. Service Factor 1.15 and Temperature rise B are applicable under the condition of sine wave power. 5. Service Factor 1.25 is applicable to motors of 100HP or less with temperature rise F & Non-Hazardous. 6. Temp. code : T3C(160°C) at sine wave				
SPARE PARTS			Date	DSND	CHKD	CHKD	APPD
			2025-09-19	S.H. LEE	I.K. KIM	R.G. KIM	S.W. KIM

[Note] Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be done according to maker standard, if not mentioned.


* In case of Inverter-Fed Motor, performance data is based on sine wave tests. It may be different from test data of Inverter combined motor.

** Data is based on rated voltage & frequency and is expressed as a percentage of full-load value.

2		3		4		
REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY

■ MAIN NAMEPLATE

3.94



■ WIRING DIAGRAM

**D.O.L
(INVERTER & SOFT STARTER)**

**WYE-DELTA
(Y-D)**

WARNING

IMPROPER INSTALLATION, CONNECTION, OPERATION, GROUNDING OF THIS MOTOR MAY CAUSE SERIOUS INJURY TO PERSONNEL OR MOTOR FAILURE. READ INSTRUCTIONS CAREFULLY. GROUNDING SHOULD BE IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE AND APPLICABLE LOCAL SOUND PRACTICES.

LOW VOLTAGE	INTERNAL CONNECTIONS	HIGH VOLTAGE

KEEP FINGERS AND FOREIGN OBJECTS AWAY FROM OPENINGS AND ROTATING PARTS DISCONNECT ALL POWER SOURCES BEFORE TOUCHING INTERNAL PARTS TO AVOID ELECTRICAL SHOCK.

4M-128845

N/A

APPD BY	S.Y.KIM	UNIT	INCH	SUBJECT	CSA Class I, Division2 Severe Duty (HES, JM/JP, 143-215)	DWG SIZE
CHKD BY	I.K.KIM	SCALE	NONE			A4 (1:1)
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle			
DSND BY	S.H.LEE	DATE	2024.06.07			
 HD HYUNDAI ELECTRIC				TITLE		
				NAMEPLATE DRAWING		
				REF. NO	4M-137664 / 4M-128845	Sheet No. of
				DWG NO	NP-HES7.5-36-213/5JP	Revision No. 0

Type : PJP

5.5kW 7.5HP

2 P

60 Hz

Full Load Torque : 10.98 lb.ft

Speed at Full Load : 3530 RPM


Load moment of Inertia (J) : 11.159 lb.ft²

Rated Voltage 575V 460V 230V


Motor moment of Inertia (J) : 0.451 lb.ft²


Full Load Current 7.26A 9.07A 18.1A

SPEED VS TORQUE & CURRENT CURVE




OUTPUT VS EFF., P.F & CURRENT CURVE





Cls. I&II, Div. 2

IEEE 841



SEC. "A" - "A"

▽	50S
▽▽	12.5S
▽▽▽	3.2S
▽▽▽▽	0.4S

REV	DATE	CONTENTS	REV'D BY	CHK'D BY	CHK'D BY	APP'D BY

일반가공공차		일반계관공차	
1-4	±0.1	6-30	±0.5
4-18	±0.2	30-120	±0.8
18-63	±0.3	120-315	±1.2
63-250	±0.5	315-1000	±2.0
250-	±0.8	1000-	±3.0

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APPD BY	S.Y.KIM	UNIT	inch(mm)	SUBJECT	FR. 210 (CAST IRON)	DWG SIZE	
CHKD BY		SCALE	1/1.5	TITLE	TERMINAL BOX ASS'Y	A3 (1:1.5)	
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle	REF. NO		Sheet No.	of
DSND BY	네슬의	DATE	2023-10-19	DWG NO	3M-248457	Revision No.	0

