

Customer :
 Project Name :
 Project No. :
 Revision No. :

SPECIFICATION for INDUCTION MOTOR



0		For Bidding			
No.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY



AC INDUCTION MOTOR DATA SHEET

IEEE841 TYPE

Catalog No.	IEEE800-36-5812S-IBSHSP	Item No.	Rev. No. []
Project Name		Project No.	Quantity sets

GENERAL SPECIFICATION		PERFORMANCE DATA					
Frame Size	5812S	Rated Output	600 kW 800 HP				
Type	HNE6	Number of Poles	2				
Enclosure(Protection)	Totally Enclosed / IP55	Rotor Type	Squirrel Cage				
Method of Cooling	IC411(FC)	Starting Method*	D.O.L				
Rated Frequency	60 Hz	Rated Voltage	575 V	460 V	230 V		
Number of Phases	3	Current	Full Load	706.6 A	883.2 A	1,766.5 A	
Insulation Class	F		Locked-rotor**	650 %	650 %	650 %	
Temp. Rise at full load (by resistance method)		Efficiency					
at 1.0 S.F	80 deg. C	50% Load		92.8 %			
Motor Location	<input type="checkbox"/> Indoor <input type="checkbox"/> Outdoor	75% Load		94.8 %			
Altitude	Less than 1,000 meter	100% Load		95.8 %			
Relative Humidity	Less than 80 %	Power Factor(p.u)					
Ambient Temp.	40 deg. C (Max.)	50% Load		0.740			
Duty Type	Continuous (S1)	75% Load		0.840			
Service Factor	1.15	100% Load		0.890			
Mounting	B3	Speed at Full Load		3570 r.p.m			
Bearing	Type	Anti-Friction					
	DE/N-DE	6316C3 / 6316C3-INS.					
	Lubricant	Grease(Polyrex-EM)					
External Thrust	Not applicable						
Coupling Method	<input checked="" type="checkbox"/> Direct <input type="checkbox"/> V-belt	Torque					
Shaft Extension	Single	Full Load		1,184.0 lb.ft			
Terminal Box	Main	Locked-rotor**		130 %			
	Aux.	Breakdown**		240 %			
Location	Refer to Outline Drawing	Moment of Inertia (J)					
Application		Load(Max.)		574.869 lb.ft2			
Area classification	Hazardous	Motor		121.840 lb.ft2			
Type of Ex-Protection	Class I, Division 2	Sound Pressure Level (No-load & mean value at 1m from motor)					
Applicable Standard	IEEE841, NEMA MG1, CSA C390	89 dB(A)					
ACCESSORIES *. Space Heater : 1EA/Motor		Vibration				3.8 mm/sec (peak)	
		Permissible number of consecutive starts		Cold	2 times		
				Hot	1 time		
		Paint	Munsell No.	7.5BG6/1.5			
		SPARE PARTS 1. Spare Axial Fan (C.W Direction)		REMARK			
				1. Premium efficiency according to NEMA MG1 2. Inverter Duty @ 1.0 Service Factor & F Temperature rise -. 10:1 VT -. 2:1 CT 3. NDE side : Insulated bearing 4. CSA Certification -. Class I, Division 2, Group A, B, C & D; Temp code : T3A 5. Shaft material : AISI4140 6. Uni-directional CCW viewed from drive end.			
		Date	DSND	CHKD	CHKD	APPD	
		2024-09-22	E.J.LEE	I.K. Kim	R.G. Kim	S.W. Kim	

ACCESSORIES		SUBMITTAL DRAWING		
*. Space Heater : 1EA/Motor		Outline Dimension Drawing \ Motor Weight(Approx.)		
		B3	LM-I5812B3CE001	6730 lb.

REMARK											
1. Premium efficiency according to NEMA MG1 2. Inverter Duty @ 1.0 Service Factor & F Temperature rise -. 10:1 VT -. 2:1 CT 3. NDE side : Insulated bearing 4. CSA Certification -. Class I, Division 2, Group A, B, C & D; Temp code : T3A 5. Shaft material : AISI4140 6. Uni-directional CCW viewed from drive end.											
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Date</td> <td>DSND</td> <td>CHKD</td> <td>CHKD</td> <td>APPD</td> </tr> <tr> <td>2024-09-22</td> <td>E.J.LEE</td> <td>I.K. Kim</td> <td>R.G. Kim</td> <td>S.W. Kim</td> </tr> </table>		Date	DSND	CHKD	CHKD	APPD	2024-09-22	E.J.LEE	I.K. Kim	R.G. Kim	S.W. Kim
Date	DSND	CHKD	CHKD	APPD							
2024-09-22	E.J.LEE	I.K. Kim	R.G. Kim	S.W. Kim							

[Note] Others not mentioned in this data sheet shall be in accordance with maker standard.
 Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.
 Inspection and performance test shall be done according to maker standard, if not mentioned.
 * In case of Inverter-Fed Motor, performance data is based on sine wave tests. It may be different from test data of Inverter combined motor.
 ** Data is based on rated voltage & frequency and is expressed as a percentage of full-load value.

	REV	DATE	CONTENTS

4.72

2.36

CROWN TRITON

Premium Efficiency AC 3 Phase Motor

800HP 2P 460V	Cat. No. IEEE800-36-5812S-IBSHSP
Model LATER	INS. Class F Amps 883.2
Type HNE6 Duty CONT	Code G Amb. 40°C Hertz 60Hz
Frame 5812S Encl. TEFC	S.F. 1.15 RPM 3570 NEMA Norm. Eff. 95.8%
Bearing	Drive 6316C3 S.F.1.00 (2:1 C.T., 10:1 V.T., NEMA-MG1 Part31) 3/4 Eff. 94.8%
	Opp. 6316C3-INS. NEMA Design B Torque
Usable at	50Hz 600HP 380V 811A 2970rpm S.F.: 1.15 Eff.: 95.8% Code: G
	50Hz 600HP 400/415V 770.45/751.06A 2972/2975rpm S.F.: 1.15 Eff.: 95.8/95.81% Code: H/J
CSA Certified for	CLASS I, Div. 2, Gr. A, B, C & D Temp. Code (sine wave) Frame 580FR
	Maximum Amb. 50°C T3A (180°C)
No. -	Date - Weight 6730 lb

IEEE Std 841-2021 4M-136445

Made in Korea H1

APPD BY	S.Y.KIM	UNIT	INCH	SUBJECT	CSA Class I, Division2 IEEE841 (XL)	DWG SIZE
CHKD BY	I.K.KIM	SCALE	NONE			A4 (1:1)
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle	NAMEPLATE DRAWING		
DSND BY	S.H.LEE	DATE	2024.06.07			
				REF. NO	4M-136445	Sheet No. of
				DWG NO	NP-IEEE800-36-5812S-IBSHSP	Revision No. 0




PERFORMANCE CURVE

CURVE NO.
PC-IEEE800-36-5812S-IBSHSP


Type :	HNE6	
Full Load Torque :	1184.0	lb.ft
Load moment of Inertia (J) :	574.869	lb.ft2
Motor moment of Inertia (J) :	121.840	lb.ft2

600kW	800HP	2 P	60 Hz
Speed at Full Load :			3570 RPM
Rated Voltage	575V	460V	230V
Full Load Current	706.6A	883.2A	1766.5A

SPEED VS TORQUE & CURRENT CURVE






OUTPUT VS EFF., P.F & CURRENT CURVE



THIS DRAWING IS PROPRIETARY TO HYUNDAI ELECTRIC. NO PART OF THIS DRAWING MAYBE REPRODUCED WITHOUT THE PERMISSION OF HYUNDAI ELECTRIC.

HD HYUNDAI ELECTRIC
 본 도면은 HD현대일렉트릭(주) 재산이며 허가없이 복사할 수 없음 (취급주의)

IEEE841



TECHNICAL INFORMATION

1) BEARING & LUBRICANT LIST

BEARING	Drive End	Non-Drive End
Bearing Type	6316C3	6316C3
Lubricant Type	GREASE	GREASE
Grease Type	Mobil(Polyrex-EM)	Mobil(Polyrex-EM)
Initial Charge Quantity	200 g	200 g
Mark-Up	Quantity	33 g
	Interval	2 MONTHS

2) TOLERANCE :

CENTER HEIGHT	14.5	+0.000	-0.060
SHAFT DIAMETER	ø2.875	+0.000	-0.001
KEYWAY WIDTH	0.75	+0.003	-0.000



VIEW "A"

SECTION "X-X"

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK
APPD BY	S.K.HAN	UNIT	INCH(MM)	SUBJECT Fr.5812-2P		
CHKD BY	S.Y.KIM	SCALE	1/12	TITLE		
CHKD BY	R.G.KIM	PROJEC'N	3각법 (3rd Angle)	OUTLINE		
DSND BY	M.S.HA	DATE	2019.05.16	REF. NO		
				DWG NO		LM-I5812B3CE001
				Sheet No. of		Revision No.

REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY
1						

**Cls. I&II, Div. 2
IEEE 841**



SEC. "A" - "A"

REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY
1						
2						
3						
4						

APPD BY	S.Y.KIM	UNIT	inch(mm)	SUBJECT	FR.580 (STEEL)	DWG SIZE	A3 (1:6)
CHKD BY		SCALE	1/6	TITLE	MAIN TERMINAL BOX ASS'Y		
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle	REF. NO		Sheet No.	of
DSND BY	박승희	DATE	2023-10-25	DWG NO	3M-248512	Revision No.	0



**Cls. I&II, Div. 2
IEEE 841**



REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY

APPD BY	S.Y.KIM	UNIT	inch(mm)	SUBJECT	FR.180 (CAST IRON)	DWG SIZE
CHKD BY		SCALE	1/1	TITLE	SUB. TERMINAL BOX ASS'Y	A3 (1:1.1)
CHKD BY	R.G.KIM	PROJEC'N	3rd Angle			
DSND BY	배승희	DATE	2024-01-18			
				REF. NO		Sheet No. of
				DWG NO	3M-165278	Revision No. 0